

Project	Part Number	Ref.
---------	-------------	------

Overview

Enclosures (CP) is a UL listed enclosure suitable for various control components. CP incorporates a standard powder coat finish on the enclosure and enclosure components. CP also includes a back plate which is a removeable component when mounting the enclosure. The enclosures feature a removeable door for accessibility.



General

Dimensions		Construction:	Type-1 Indoor-Dry, 18ga With Powder Coat Finish
A	07.125 x 11.75 x 4.75	Mounting:	Surface
B	07.125 x 14.25 x 4.75	Weight:	Configuration Dependent
C	11.750 x 14.25 x 4.75		
D	18.750 x 14.25 x 4.75		
E	25.750 x 14.25 x 4.75		
F	32.750 x 14.25 x 4.75		

Capacities

Size A, B Include (1) DIN Rail, Size C - F Include (2) DIN Rails With Barriers For Voltage And Class Separation.

I/O Modules	0-32	Size	Class-I Slots	Class-II Slots
		A	3	3
		B	3	4
		C	4	5
		D	8	9
		E	12	13
		F	16	17

Environmental

Ambient Temperature	0 - 130 °F
Relative Humidity (non-condensing)	5 - 95%
Plenum Rated	Yes

Certifications and Listings

UL/CL	UL 916, 508A	Seismic	2012 ICC-ES AC156, Importance Factor 1.5
-------	--------------	---------	--

Ordering Information

ENCL
 A

Selections

Options	
A Packaging	A - F