

Project	Part Number	Ref.
---------	-------------	------

AO08 is a 0-10V Analog Output module used for 0-10VDC dimming applications. AO08 is a standard I/O Module option for all control products. AO08 is combined with other I/O modules via a pluggable CANbus to address specific application requirements. Remote mounting applications require a Termination Module (TM).

- Standard Panel and Kit Option
- DIN Rail Mounted
- Resides on CANbus Network
- 8 Analog Outputs
- Rotary Dial Addressing
- Remote Configuration



General

Device Type	Class II	Mounting	DIN Rail
Dimensions	3.50" x 2.50"	Weight	2.7 oz
Wire Requirement	See Cabling Data Sheet		

Power

Input	24VDC, 84mA Requires TM01 or TM03	Output	8 Analog Outputs 0-10VDC Sink 100mA or Source 5mA Each
-------	--------------------------------------	--------	---

Communication

CANbus	
Baud Rate	125kbps
Address	Rotary, Range 1 - 32
Topology	Daisy Chain

Environmental

Ambient Temperature	0 - 130 °F
Relative Humidity (non-condensing)	10 - 90%
Plenum Rated	Yes

Certifications and Listings

UL/CL	UL916	Seismic	2012 ICC-ES AC156, Importance Factor 1.5
-------	-------	---------	--

Ordering Information

AO08	Analog Output Module (8) Outputs Each, 0-10VDC
------	--