

Project	Part Number	Ref.
---------	-------------	------

Capacitive Touch Stations (CTS-DDN) provide local occupant interface via the DDN Network. Station applications are software configurable, eliminate home run wiring, utilize capacitive touch technology with no mechanical parts to extend service life.



Applications

- On/Off
- Override
- Three and Four Way Operation

General

- Fits Decorator Style Wall/Face Plates
- Gangable with other Decorator Style Devices
- Audible Chip Indication on Button Press
- LED Indication of Status
- LED Indication on Transition

General

Device Type	Class II	Mounting	Junction Box, 6/32 Machine Screw
Construction	Acrylic Face Mount in an Open Steel Frame	Weight	1.2 oz.
Dimensions	4.13" x 1.60" x 1.00"		

Capacities

CTS1CH	1-Button On/Off
CTS2CH	2-Button On/Off

Power

Input	24VDC, 15mA
Output	N/A

Communication

DDN Network	
Baud Rate	19200 bps
Address	Dip Switch, Range 1 - 60
Topology	Daisy Chain

Compatibility

Legacy Products	LX Platform
-----------------	-------------

Environmental

Ambient Temperature	0 - 130 °F
Relative Humidity (non-condensing)	5 - 95%
Plenum Rated	No

Certifications

N/A

Warranty

Two Years From Date of Shipment


Ordering Information

CTS - W H - D D N
A B C


Options

- A Channel Quantity: 1 or 2
- B Station Configuration: CH

Layout Options



CTS1CH



CTS2CH